

***Tehnička specifikacija računalne  
opreme, programa i pribora  
– Informatička oprema***

# 1. Tehnička sredstva

Br.	Naziv artikla / specifikacija	Količina komada	Jedinična cijena	Ukupna cijena
1.	<b>Kopirni uređaj</b>	1		
	Proces kopiranja	Laserski uređaj		
	Brzina	19 kopija u minuti (18 kpm jedan na jedan kopiranje)		
	Rezolucija	600 dpi		
	Višestruko kopiranje	Do 99		
	Vrijeme zagrijavanja	Manje od 10 sekundi		
	Brzina prve kopije	Manje od 6.5 sekundi		
	Zoom	50 - 200% (u koracima od 1%)		
	Memorija	16 MB		
	Ulazni kapacitet	Standard: 1 x 250-listova u ladicu		
		100-listova u ručni ulagač		
		Maksimalno: 350 listova		
	ADF kapacitet	30 listova		
	Izlazni kapacitet papira	Standard: 250 listova (unutrašnja ladica)		
	Veličina papira	Ladica: A5 - A3		
		Ručni ulagač: A6 - A3		
	Težina papira	Ladica: 60 - 90 g/m <sup>2</sup>		
		Ručni ulagač: 52 - 162 g/m <sup>2</sup>		
	Uvećanje/umanjenje	4 smanjenja, 3 uvećanja		
	Dimenzije (Š x D x V)	550 x 568 x 420 mm		
	Težina	35 kg ili manje		
	Izvor napajanja	220 - 240 V, 50 - 60 Hz		
	Potrošnja	Manje od 1.28 kW		
	POTROŠNI MATERIJAL			
	Crni toner	9,000 listova <sup>1</sup>		
	DODATNA OPREMA	Poklopac, 30-listova automatski dodavač papira, Ručke za pristupačnost, Postolje		

Br.	Naziv artikla / specifikacija	Količina komada	Jedinična cijena	Ukupna cijena
2.	<b>Monitor</b>	25		
	<b>DISPLAY</b>			
	Diagonal Viewable Size:	21.5 inches (21.5- inch wide viewable image size) (54.61 cm)		
	Panel Type, Surface:	IPS (In-Plane Switching), anti glare with hard coat 3H		
	Optimal Resolution:	Full HD resolution, 1920 x 1080 at 60 Hz		
	Preset Display Area ( H x V)	476.57mm x 268.76mm 18.76" x 10.58"		
	Contrast Ratio:	1000: 1 (typical), Dynamic Contrast Ratio: 2 Million:1 (Max)		
	Brightness:	250 cd/m2 (typical)		
	Response Time:	8ms (gray to gray)		
	Viewing Angle	(178° vertical / 178° horizontal)		
	Color Support:	Color Gamut (typical): 82% (CIE 1976)1 Color Depth: 16.7 million colors		
	Pixel Pitch:	0.2475mm		
	Backlight Technology	LED		
	<b>COLOR, SIZE AND WEIGHT</b>			
	Dimensions with stand (HxWxD)	355.6 mm(compressed) ~484.5 mm(extended) x 513.0 mm x 183.3 mm mm 14.00 inches (compressed) ~19.07 inches(extended) x 20.20 inches x 7.22 inches		
	Dimensions without stand (HxWxD)	304.5mm x 513.0mm x 59.5 mm 11.99 inches x 20.20 inches x 2.34 inches		
	Weight (panel only - for VESA mount)	2.7 kg 6.0 lbs		
	Weight (with packaging)	6.8kg 15.0 lbs		
	Specifications - Service / Support Details	3-Year Advanced Exchange5 Service and Premium Panel Guarantee		
	<b>ENVIRONMENTAL</b>			
	Temperature Range Operating:	0° to 40°C (32° to 104°F)		
	Temperature Range Non-operating:	Storage : -20° to 60° (-4° to 140° F) Shipping : -20° to 60° (-4° to 140° F)		
	Humidity Range Operating:	10% to 80% (non-condensing)		
	Humidity Range Non-operating:	Storage : 5% to 90% (non-condensing) Shipping : 5% to 90% (non-condensing)		
	Altitude Operating:	3,048 m (10,000 ft) max		
	Altitude Non-operating:	10,668 m (35,000 ft) max		
	<b>OTHER</b>			
	CONNECTIVITY	1 Digital Visual Interface connectors (DVI-D) with HDCP 1 DisplayPort (DP) 1 Video Graphics Array (VGA) 1 USB 2.0 upstream port 4 USB 2.0 downstream ports DC power connector for Dell Soundbar		

	DC out
COMPLIANCE AND STANDARDS	ENERGY STAR 5.0
	EPEAT Gold
	TCO Certified Displays
WHAT'S IN THE BOX	Monitor with stand
	Power Cable
	DVI Cable
	USB Cable
	VGA Cable
	Drivers and Documentation media
	Quick Setup Guide
	Safety Information
STAND	Height-Adjustable stand, tilt , swivel , pivot and built in cable-management.
SECURITY	Security lock slot (cable lock sold separately)
	Anti-theft stand lock slot (to panel)
BUILT-IN DEVICES	USB 2.0 Hi-Speed Hub (with 1 USB upstream port and 4 USB downstream ports)

Br.	Naziv artikla / specifikacija		Količina komada	Jedinična cijena	Ukupna cijena
3.	<b>Radna stanica</b>		10		
	CPU tip:	Intel® Core™ i3			
	CPU brand:	Intel			
	CPU model: 2120	2120			
	CPU brzina [GHz]:	3,33			
	L2 Cache:	4x 256 KB			
	L3 Cache:	3 MB			
	Chipset:	Intel Q67 Express			
	Socket:	1155			
	Količina memorije:	1x 2 GB			
	Tip memorije:	DDR3			
	Takt memorije [MHz]:	1333			
	Broj memorijskih utora:	4			
	Maksimalna količina memorije [GB]	16			
	Grafička kartica:	Integrirana			
	Model grafičke kartice:	Intel® HD 2000			
	Tip čvrstog diska:	SATA			
	Veličina diska [GB]:	500			
	Broj okretaja diska:	7.200 o/min			
	Optički uređaj:	DVD±RW DL			
	Zvučna kartica:	High Definition Audio with Realtek ALC261 codec; Microphone/Headphone* and dedicated headphone front ports (3.5mm); Multi-streaming capable; Internal Speaker (standard)			
	Mrežna kartica - model:	Intel 82579LM GbE integrated network connection			
	Mrežna kartica - brzina [Mbit]:	10/100/1000			
	WLAN mreža:	n/a			
	Utori za proširenje:	1x PCIe x 1			
	Interni konektori:	4 x SATA			
	Stražnji panel:	1x RJ45			
	Prednji panel:	4x USB			
	Kućište - veličina:	Convertible Mini Tower			
	Napajanje [W]:	320			
	Ladica za uređaje 5,25" vanjska:	3			
	Ladica za uređaje 3,5" interna:	3			
	Miš:	HP PS/2 Optical Mouse			
	Tipkovnica:	HP PS/2 Standard Keyboard			
	Zvučnici:	Internal Speaker			
	Ostale značajke:	ENERGY STAR qualified; integrirana RAID podrška			
	OS:	Windows® 7 Professional			

Br.	Naziv artikla / specifikacija		Količina/ komada	Jedinična cijena	Ukupna cijena
4.	<b>Prijenosno računalo 1</b>		30		
	Procesor:	Intel® Core™ i5-2430M 2.4 / 3.0 Turbo GHz, 3 MB Level 3 Cache			
	Chipset:	Mobile Intel® HM65 Express			
	Ekran:	17.3" LED-backlit HD+ anti-glare 1600 x 900, 720p HD webcam			
	Memorija:	4 GB 1333 MHz DDR3 SDRAM, max 8 GB DDR3			
	Hard disk:	640 GB 5400 rpm SATA II			
	Optički uređaj:	DVD+/-RW SuperMulti DL			
	Grafika:	AMD Radeon HD 6490M with 1 GB dedicated GDDR5 video memory			
	Zvuk:	SRS Premium Sound, Integrated stereo speakers, Stereo headphone/line out, Stereo microphone in, Integrated microphone (dual-microphone array with optional webcam)			
	Mreža:	Realtek Ethernet (10/100/1000 NIC)			
	Bežična mreža:	Atheros 802.11b/g/n WiFi			
		Bluetooth 3.0 HS Combo			
	Portovi:	4 x USB 2.0			
		1 x stereo headphone/line out			
		1 x stereo microphone in			
		1 x LAN RJ-45			
		1 x VGA (15-pin mini D-Sub)			
		1 x HDMI			
	Baterija:	8-cell (73 WHr) Lithium-Ion Battery do max. 6h			
	Dimenzije:	41.4 x 27.9 x 2.9 cm			
	Težina:	od 2,92 kg			
	Operativni:	Windows® 7 Professional 64bit			
	Jamstvo:	36 mjeseci			
	Ostalo	ExpressCard/34 slot			
		Media Card Reader			
		Spill-resistant keyboard with separate numeric keypad and drains			
		Touchpad with scroll zone and gestures support			
		720p HD webcam			
		Torba HP Basic Messenger Case			

Br.	Naziv artikla / specifikacija		Količina/ komada	Jedinična cijena	Ukupna cijena
5.	<b>Prijenosno računalo 2</b>		5		
	Procesor	Intel Core i3-2330M (2.20 GHz, 3 MB L3 cache)			
	Tehnologija	Intel			
	Chipset	Intel HM65 Express			
	Sistemska memorija	4 GB DDR3			
	Hard Disk	320 GB SATA II			
	Optički uređaj	DVD+/-RW SuperMulti DL			
	Zaslon	13.3" LED-backlit HD anti-glare			
	Grafika	Intel HD Graphics 3000			
	Audio	SRS Premium Sound			
	Zvučnici	Integrated stereo speakers			
	Mreža	10/100/1000 Gigabit Ethernet LAN			
	Bežična mreža	802.11 b/g/n, Bluetooth			
	Modem	/			
	I/O Portovi	3 USB 2.0; 1 USB 3.0; 1 VGA; 1 HDMI; 1 stereo microphone in; 1 stereo headphone/line-out; 1 AC power; 1 RJ-11 (select models); 1 RJ-45			
	Ostalo	1 Express Card/34; 1 Media Card Reader, 720p HD webcam, Spill-resistant keyboard with numeric keypad and drains, Touchpad with scroll zone and gestures support, ENERGY STAR, torba			
	Baterija	6-cell Lithium-Ion (Li-Ion) battery			
	Autonomija	Do 6 sati autonomije baterije			
	Dimenzije	33 x 23.5 x 2.79 cm			
	Težina	od 2 kg			
	Boja	Tamno siva			
	Operativni sustav	Windows 7 Professional 64			
	Jamstvo	36 mjeseci			

Br.	Naziv artikla / specifikacija	Količina/ komada	Jedinična cijena	Ukupna cijena
6.	<b>Prijenosno računalo 3</b>	3		
	Procesor:	Intel Core i7-2670QM 2,2 / 3,1 Turbo GHz, 2nd level cache :6 MB		
	Ekran:	15.6" LED-backlit FHD WVA anti-glare (1920 x 1080), integrated HD webcam		
	Memorija:	4 + 4 GB 1333 MHz DDR3 SDRAM, max 32 GB		
	Hard disk:	500 GB 7200 rpm SATA II		
	Optički uređaj:	DVD+/-RW SuperMulti DL		
	Grafika:	NVIDIA Quadro 1000M with 2 GB dedicated DDR3 video memory		
	Zvuk:	SRS Premium Sound; Integrated stereo speakers; Dual-microphone array; Button for volume mute; function keys for volume up and down; Stereo headphone/line out; Stereo microphone/line in		
	Mreža:	Integrated Intel 82579LM Gigabit Network Connection (10/100/1000 NIC)		
	Modem:	da		
	Bežična mreža:	Intel Centrino 802.11a/b/g/n HP Integrated Module with Bluetooth 2.1+EDR Wireless Technology		
	Portovi:	2 x USB 3.0		
		1 x USB 2.0		
		1 x eSATA/USB 2.0 Combo		
		1 x USB 2.0 charging		
		1 x DisplayPort		
		1 x external VGA monitor		
		1 x 1394a firewire		
		1 x stereo microphone in		
		1 x stereo headphone/line-out		
		1 x AC power		
		1 x RJ-11		
		1 x RJ-45		
		1 x docking connector		
		1 x secondary battery connector		
		Ostalo	1 x Express Card/54	
	1 x Smart Card Reader			
	SD/MMC Card Reader			
	HD webcam			
		HP Fingerprint Sensor		
		Wireless Desktop MK710 (keyboard + mouse) with unified receiver		
	Baterija:	Long Life 8-cell (75 WHr) Li-Ion battery		
	Dimenzije:	38.2 x 25.75 x 3.45 cm		
	Težina:	od 2.9 kg		
	Torba:	da		
	Operativni sustav:	Windows® 7 Professional 64		
	Docking station:	Expansion slots: SATA upgrade bay		



	Ports: 6 USB 2.0 ports (5 Always-On, 1 powered); 1 eSATA adapter; 1 Line-in jack; 1 Audio-out (headphone) jack; 2 DisplayPort; 1 VGA; 2 DVI-D; AC adapter connector with light; 1 Mouse connector; 1 Keyboard connector; 1 Parallel port; 1 Serial port; 1 Monitor stand port; 1 RJ-45 (network) jack
	Power requirements: Rated Voltage: 100 to 240 V; Rated Current: 2.5A rms; Line Frequency: 50 - 60 Hz
	Product dimensions (W x D x H): 2.60 x 10.65 x 10.24 in
	Security management: Supports the HP Docking Station Cable Lock, which gives you two security options: lock the docking station only (which also prevents access to the Advanced Docking Station drive bay); or lock both the docking station and your notebook for additional security. Also supports an industry standard notebook lock.
	Weight ( Metric ): 1.637 kg
Jamstvo:	36 mjeseci

Br.	Naziv artikla / specifikacija	Količina/ komada	Jedinična cijena	Ukupna cijena
7.	<b>Prijenosno računalo 4</b>	3		
	Procesor:	Intel Core i7-2670QM 2,2 / 3,1 Turbo GHz, 2nd level cache :6 MB		
	Chipset:	Mobile Intel® QM67 Express Chipset		
	Ekran:	17.3" LED-backlit FHD WVA anti-glare (1920 x 1080), HD webcam		
	Memorija:	4 + 4 GB 1333 MHz DDR3 SDRAM, max 32 GB		
	Hard disk:	500 GB 7200 rpm SATA II		
	Optički uređaj:	DVD+/-RW SuperMulti DL		
	Grafika:	AMD FirePro M5950 with 1 GB dedicated GDDR5 video memory		
	Zvuk:	SRS Premium Sound; Integrated stereo speakers; Dual-microphone array; Button for volume mute; function keys for volume up and down; Stereo headphone/line out; Stereo microphone/line in		
	Mreža:	Integrated Intel 82579LM Gigabit Network Connection (10/100/1000 NIC)		
	Modem:	da		
	Bežična mreža:	Intel Centrino 802.11a/b/g/n HP Integrated Module with Bluetooth 2.1+EDR Wireless Technology		
	Portovi:	2 USB 3.0		
		1 USB 2.0		
		1 USB 2.0 charging		
		1 eSATA/USB combo		
		1 external VGA monitor		
		1 DisplayPort		
		1 1394a		
		1 stereo microphone in		
		1 stereo headphone/line-out		
		1 AC power		

	1 RJ-11
	1 RJ-45
	1 docking connector
	1 secondary battery connector
	1 x Express Card/54
	1 x Smart Card Reader
	1 SD/MMC
Ostalo:	HP Fingerprint Sensor
	HD webcam
	Full-sized spill-resistant keyboard with separate numeric keypad and drain
	Touchpad with on/off button, two-way scroll, gestures, three pick buttons; Pointstick with three additional pointstick buttons
	Wireless Desktop MK710 (keyboard + mouse) with unified receiver
Baterija:	HP Long Life 8-cell (75 WHr) Li-Ion battery
Dimenzije:	41.65 x 27.27 x 3.74 cm
Težina:	3.47 kg
Operativni:	Windows® 7 Professional 64
Torba:	da
Docking station	Expansion slots: SATA upgrade bay
	Ports: 6 USB 2.0 ports (5 Always-On, 1 powered); 1 eSATA adapter; 1 Line-in jack; 1 Audio-out (headphone) jack; 2 DisplayPort; 1 VGA; 2 DVI-D; AC adapter connector with light; 1 Mouse connector; 1 Keyboard connector; 1 Parallel port; 1 Serial port; 1 Monitor stand port; 1 RJ-45 (network) jack
	Power requirements: Rated Voltage: 100 to 240 V; Rated Current: 2.5A rms; Line Frequency: 50 - 60 Hz
	Product dimensions (W x D x H): 2.60 x 10.65 x 10.24 in
	Security management: Supports the HP Docking Station Cable Lock, which gives you two security options: lock the docking station only (which also prevents access to the Advanced Docking Station drive bay); or lock both the docking station and your notebook for additional security. Also supports an industry standard notebook lock.
	Weight ( Metric ): 1.637 kg
Jamstvo:	36 mjeseci

Br.	Naziv artikla / specifikacija	Količina/ komada	Jedinična cijena	Ukupna cijena
8.	<b>Projektor</b>	1		
	Technical Information			
	Projection Method	Ceiling		
		Front		
		Rear		
	3D Ready	Yes		
	Platform Supported	Mac		
		PC		
	Lens			
	Minimum Lens Aperture	F/2.5		
	Maximum Lens Aperture	F/2.6		
	Zoom Type	Digital Zoom		
		Manual Zoom		
	Manual Zoom Factor	1.1x		
	Digital Zoom Factor	2x		
	Lamp			
	Lamp Type	OSRAM		
	Lamp Power	240 W		
	Normal Mode Lamp Life	3500 Hour		
	Economy Mode Lamp Life	5000 Hour		
	Image			
	Standard Mode Brightness	3100 lm		
	Low Mode Brightness	2480 lm		
	Colour Support	1.07 Billion Colors (30-bit)		
	Native Resolution	1280 x 800		
	Graphic Mode	WXGA		
	Maximum Resolution	1600 x 1200		
	Minimum Projection Distance	1 m		
	Maximum Projection Distance	10 m		
	Diagonal Image Size	762 cm (300")		
	Native Aspect Ratio	16:10		
	Compatible Aspect Ratio	4:03		
		16:09		
	Contrast Ratio	10000:1		
	Uniformity	90%		
	Vertical Keystone Correction	-40°/+40°		
	Maximum Vertical Sync	120 Hz		
	Maximum Horizontal Sync	100 kHz		
	Video			
	Video Signal Format	NTSC		

	PAL
	SECAM
Video Signal Standard	HDTV
Scan Format	1080p
Audio	
Number of Speakers	1
Speaker Output Power	2 W
Speaker Output Mode	Mono
Power Description	
Input Voltage	220 V AC
	110 V AC
Physical Characteristics	
Weight (Approximate)	2.52 kg
Miscellaneous	
Package Contents	P1303PW DLP Projector
	AC Power Cord
	VGA Cable
	Remote Control
	2 x Battery for Remote Control
	Lens Cap
	Carrying Case
	User's Guide (CD-ROM)
	Quick Start Guide
	Security Card
Warranty	Two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

Br.	Naziv artikla / specifikacija		Količina/ komada	Jedinična cijena	Ukupna cijena
9.	<b>Security appliance</b>		1		
	Product Type	Security Appliance			
	Bundled with	Advanced Inspection and Prevention Security Services Module 10 (AIP-SSM-10)			
	Number of Expansion Slots	2			
	Ethernet Port	Yes			
	Fast Ethernet Port	Yes			
	Gigabit Ethernet Port	Yes			
	VPN Throughput	170 Mbps			
	Encryption Standard	3DES			
		AES			
	Firewall Throughput	300 Mbps			
	Memory Technology	DRAM			
	Product Series	5500			
	Input Voltage Range	100 V AC to 240 V AC			
	Form Factor	Rack-mountable			
		Desktop			
	Number of Ports	5			
	Dimensions	1.8" Height x 17.5" Width x 14.3" Depth			
	Firewall Protection	Intrusion Prevention			
		Antivirus			
		Access Control			
		Worm Scanning			
	Flash Memory	64 MB			
	Input Voltage	110 V AC			
		220 V AC			
	License Type	Unlimited User License			
	Interfaces/Ports	2 x RJ-45 10/100/1000Base-T Network LAN			
		3 x RJ-45 10/100Base-TX Network LAN			
		1 x RJ-45 Auxiliary Management			
		1 x RJ-45 Console Management			
		2 x USB 2.0			
	Power Source	Power Supply			
	Standard Memory	256 MB			
	Compatible Rack Unit	1U			
	Management	Adaptive Security Device Manager			
	Expansion Slots	(1 Total) SSM			
		(1 Total) CompactFlash (CF) Card			
	Processor	1 x Intel Celeron 1.60 GHz			
	Virtualization	50000 x Concurrent Connection			
		50 x 802.1Q VLAN Support			
		250 x IPSec VPN Peer			
		9000 x Connections Per Second			

	2 x SSL VPN Peer
VPN Supported	Scalable IPSec and SSL VPN services
	Remote user/site connectivity
Product Family	5500
Additional Information	SKU ASA5510-AIP10SP-K9
	IPS software version SF-ASA-AIP-7.0-K9
	ASA software version 8.2(5)
Warranty	1 year

Br.	Naziv artikla / specifikacija		Količina/ komada	Jedinična cijena	Ukupna cijena
10.	<b>L3 switch</b>		2		
	Humidity Range Operating	10 - 85%			
	Max Altitude Operating	9840 ft			
	Max Operating Temperature	113 °F			
	Min Operating Temperature	32 °F			
	Connector Type	RJ-45			
	Interface	Ethernet 10Base-T/100Base-TX/1000Base-T			
	Port Quantity	24			
	Cabling Type	Ethernet 1000Base-T , Ethernet 100Base-TX , Ethernet 10Base-T			
	Communication Mode	Full-duplex , Half-duplex			
	Compliant Standards	IEEE 802.1D , IEEE 802.1p , IEEE 802.1Q , IEEE 802.1s , IEEE 802.1w , IEEE 802.1x , IEEE 802.3 , IEEE 802.3ab , IEEE 802.3ad (LACP) , IEEE 802.3u , IEEE 802.3z			
	Connectivity Technology	Wired			
	Data Link Protocol	Ethernet , Fast Ethernet , Gigabit Ethernet			
	Data Transfer Rate	1 Gbps			
	Empty Slots	4 x SFP (mini-GBIC)			
	Features	ARP support , Auto-negotiation , Auto-sensing per device , DHCP support , Flow control , Full duplex capability , IGMP snooping , Load balancing , Manageable , Routing , Stackable , Trunking , VLAN support			
	Form Factor	Rack-mountable			
	MAC Address Table Size	12K entries			
	Remote Management Protocol	RMON , RMON 2 , SNMP , SNMP 1 , SNMP 2 , SNMP 3 , Telnet			
	Routing Protocol	HSRP , RIP-1 , RIP-2 , Static IP routing			
	Stackable	Yes			
	Status Indicators	Link activity , Port duplex mode , Port status , Port transmission speed , Power			
	Subcategory (FE)	Network hubs and switches			
	Power Form Factor	Internal			
	Power Frequency Required	50/60 Hz			
	Nominal Voltage	AC 120/230 V			
	Power Consumption Operational	165 Watt			
	Software Type	Cisco IOS IP Base			
	Depth	11.6 in			
	Height	2.6 in			
	Width	17.5 in			
	Flash Memory Installed Size	16 MB			
	Installed DRAM Memory Size	128 MB			
	Authentication Method	RADIUS , Secure Shell (SSH) , TACACS+			

Compliant Standards	CE , CISPR 24 , CSA , cUL , EN 60950 , EN55022 , EN55024 , FCC Class A certified , IEC 60950 , NOM , TUV GS , UL , VCCI Class A ITE
Height (Rack Units)	1.5
MTBF	188,574 hour(s)
SKU	WS-C3750G-24T-S

Br.	Naziv artikla / specifikacija	Količina/ komada	Jedinična cijena	Ukupna cijena
11.	<b>Fotoaparat</b>	1		
	<b>Imaging</b>			
	Camera Type	Digital SLR with Interchangeable lenses		
	Lens Mount	Nikon F		
	Camera Format	DX / (1.5x Crop Factor)		
	Resolution	Effective Pixels: 16.2 Megapixels		
	Sensor Type / Size	CMOS, 23.6 x 15.6 mm		
	File Formats	Still Images: JPEG, RAW Movies: MPEG-4 AVC/H.264, MOV		
	Bit Depth	14-bit		
	Memory Card Type	SD SDHC SDXC 1		
	<b>AV Recording</b>			
	Video Recording	Yes, NTSC/PAL		
	Aspect Ratio	03:16,2		
	Video Clip Length	Up to 20 Minutes Limited by Memory Card Capacity		
	Audio Recording	With Video, Mono		
	<b>Focus Control</b>			
	Focus Type	Auto & Manual		
	<b>Viewfinder/Display</b>			
	Viewfinder Type	Pentaprism		
	Viewfinder Coverage	100%		
	Display Screen	3" Rear Screen LCD (921000)		
	Screen Coverage	100%		
	<b>Exposure Control</b>			
	ISO Sensitivity	100-25600		
	Shutter	30 - 1/8000 sec		
	Mirror Lock-Up	Yes		
	Metering Method	Spot metering, Center-weighted average metering, 3D Color Matrix Metering		
	Exposure Modes	Modes: Aperture Priority, Auto, Manual, Program, Shutter Priority		
	White Balance Modes	Auto, Cloudy, Flash, Fluorescent, Fluorescent (Day White), Fluorescent (Natural White), Fluorescent (White), Fluorescent H, Incandescent, Shade, Preset Manual		
	<b>Flash</b>			
	Max Sync Speed	1 / 250 sec		



Continuous Shooting	Up to 6 fps
External Flash Connection	Hot Shoe, Wireless
<b>Performance</b>	
Self Timer	2 sec, 5 sec, 10 sec, 20 sec
Connectivity	AV Output, USB 2.0
Software Requirements	Windows: XP, Vista, 7 Mac: OS X 10.4.11 or later
<b>Power</b>	
Battery	1x EN-EL15 Rechargeable Lithium-Ion Battery Pack
<b>Physical</b>	
Dimensions (WxHxD)	5.2 x 4.2 x 3" / 13.21 x 10.67 x 7.62 cm
Weight	1.71 lb / 779 g Camera with battery and memory card
<b>Kit Lens</b>	
Focal Length	18 - 105 mm Comparable DX Focal Length: 27 - 157 mm
Aperture	Maximum: f/3.5 - 5.6 Minimum: f/22 - 22
Minimum Focus Distance	1.5' (45.72 cm)
Autofocus	Yes
<b>Other</b>	
Extra included	1 x Rechargeable Li-ion Battery EN-EL15
	Battery Charger MH-25
	Eyepiece Cap DK-5
	Rubber Eyecup DK-21
	USB Cable UC-E4
	Audio Video Cable EG-D2
	Camera Strap AN-DC1
	LCD Monitor Cover BM-11
	Body Cap BF-1B
	Accessory Shoe Cover BS-1
	ViewNX 2 CD ROM
	8 GB Extreme SDHC Class 10 Memory Card
	AF-S DX VR Zoom-Nikkor 55-200mm f/4-5.6G IF-ED (3.6x)
	Rezo TLZ 20 Compact Holster-Style Bag
1 year warranty	

Br.	Naziv artikla / specifikacija		Količina/ komada	Jedinična cijena	Ukupna cijena
12.	<b>Bljeskalica</b>		1		
	Elektronička konstrukcija	Automatski IGBT tranzistor (engl. Insulated Gate Bipolar Transistor) i serijski sklop			
	Broj vodiča (na 35-milimetarskom položaju glave zuma, u FX formatu, uzorak Standardnog osvjetljenja, 20 °C/68 °F)	34/111,5 (ISO 100, m/ft), 48/157,5 (ISO 200, m/ft)			
	Efektivna udaljenost izlazne razine bljeskalice (u i-TTL, bljeskalici za autom. ekspoziciju, autom. bljeskalici bez TTL-a)	Od 0,6 m do 20 m (od 2 ft do 66 ft) (razlikuje se ovisno o postavci slike fotoaparata, uzorku osvjetljenja, ISO osjetljivosti, položaju glave zuma i otvoru objektiva koji se upotrebljava)			
	Uzorak osvjetljenja	Postoje tri uzorka osvjetljenja: standardno, ravnomjerno i centrirano. Kut raspodjele svjetlosti automatski se prilagođava slikovnom području fotoaparata u FX i DX formatima			
	Dostupni načini rada bljeskalice	i-TTL, automatski otvor objektiva s bljeskalicom, automatska bljeskalica koja nije TTL, ručna bljeskalica s prioritetom udaljenosti i opetovana bljeskalica			
	Ostale dostupne funkcije	Probno okidanje, nadzor bljeskanja unaprijed, osvjetljenje uz pomoć AF-a za AF s više točaka i oblikovanje osvjetljenja			
	Nikonov sustav kreativnog osvjetljenja	Razni načini rada s bljeskalicom dostupni su s kompatibilnim fotoaparatima: i-TTL način rada, Napredno bežično osvjetljenje, FV zaključavanje, flash color information communication (Komunikacija putem informacija boje bljeskalice), automatska FP sinkronizacija velike brzine i osvjetljenje uz pomoć AF-a za AF s više točaka			
	Rad s fotografijom s višestrukom bljeskalicom	Napredno bežično osvjetljenje fotografija s bežičnom višestrukom bljeskalicom vrste SU-4			
	Upravljanje ekspozicijom bljeskalice postavljeno na fotoaparatu	Načini sinkronizacije fotoaparata: spora sinkronizacija, spora sinkronizacija sa smanjenjem efekta crvenih očiju, sinkronizacija prednje zavjese, sinkronizacija stražnje zavjese, spora sinkronizacija stražnje zavjese Funkcije fotografije: automatska FP sinkronizacija velike brzine, FV zaključavanje, smanjenje efekta crvenih očiju			
	Mogućnosti odskakanja	Glava bljeskalice naginje se prema dolje do 7 ° ili do 90 ° sa zaustavljanjem uz zvučni klik na -7 °, 0 °, 45 °, 60 °, 75 °, 90 °. Glava bljeskalice okreće se vodoravno za 180 ° ulijevo i udesno sa zaustavljanjima uz zvučni klik na 0 °, 30 °, 60 °, 75 °, 90 °, 120 °, 150 °, 180 °			
	Uključivanje/isključivanje napajanja	Okrenite prekidač napajanja/bežični način rada za više jedinica bljeskalice kako biste uključili ili isključili SB-910 Može se podesiti i funkcija Pripravnosti			
	Izvor napajanja	Koristite četiri baterije tipa AA iste marke jedne od sljedećih vrsta: 1.5 V LR6 (tipa AA) alkalne baterije 1.5 V FR6 (tipa AA) litijske baterije 1.2 V HR6 (tipa AA) punjive Ni-MH baterije			
	Pokazivač spremnosti bljeskalice	SB-910 je u potpunosti recikliran: uključuje se Nedovoljna izlazna razina bljeskalice za ispravnu ekspoziciju (u i-TTL, bljeskalici za automatsku ekspoziciju, automatskoj bljeskalici bez TTL-a ili načinu ručne bljeskalice s prioritetom udaljenosti): trepće			

Pokazivač spremnosti bljeskalice (u udaljenom snimanju)	SB-910 je u potpunosti recikliran: trepće Nedovoljna izlazna razina bljeskalice za ispravnu ekspoziciju (u i-TTL, bljeskalici za automatsku ekspoziciju, automatskoj bljeskalici bez TTL-a ili automatskom načinu u fotografiji s bežičnom višestrukom bljeskalicom vrste SU-4): trepće
Trajanje bljeskalice (pribl.)	1/880 s za M1/1 (potpuni) izlaz 1/1100 s za M1/2 izlaz 1/2550 s za M1/4 izlaz 1/5000 s za M1/8 izlaz 1/10000 s za M1/16 izlaz 1/20000 s za M1/32 izlaz 1/35700 s za M1/64 izlaz 1/38500 s za M1/128 izlaz
Ručka montažnog postolja	Omogućuje sigurno postavljanje SB-910 na dodatni nastavak za stativ pomoću ploče i klina za pričvršćivanje kako bi se spriječilo slučajno odvajanje
Kompenzacija bljeskalice	-3.0 EV do +3.0 EV u koracima od 1/3 EV koraka u i-TTL, bljeskalici za automatsku ekspoziciju, automatskoj bljeskalici bez TTL-a ili načinu ručne bljeskalice s prioritetom udaljenosti
Prilagođene postavke	19 stavki
Ostale funkcije	Ručna postavka ISO osjetljivosti, ponovni prikaz smanjene ekspozicije zbog nedovoljne izlazne razine bljeskalice u i-TTL načinu, vraćanje na zadane postavke, zaključavanje tipkovnice, toplinsko isključivanje, ažuriranje firmvera
Dimenzije (Š x V x D)	Pribl. 78,5 x 145 x 113 mm (3.1 x 5.7 x 4.4 in.)
Težina	Pribl. 510 g (18 oz) (s četiri 1.5 V LR6 (tip AA) alkalne baterije) Pribl. 420 g (14.8 oz) (samo bljeskalica Speedlight)
Priložena oprema	Postolje bljeskalice Speedlight AS-21, Nikonov difuzor SW-13H, Filtar fluorescentnog svjetla SZ-2FL, Filtar žarne niti SZ-2TN, Mekana torbica SS-910

<b>UKUPNO TEHNIČKA SREDSTVA (bez PDV-a):</b>	
[slovima: _____ ]	

## 2. Informatičke komponente

Br.	Naziv artikla / specifikacija	Količina	Jedinična cijena	Ukupna cijena
	<b>Informatičke komponente</b>			
1.	<p>Tipkovnica</p> <p><i>Interface: USB</i></p> <p><i>Additional keys: E-mail , Volume , Calculator , Multimedia , Internet browsing</i></p> <p><i>Colour: black</i></p> <p><i>Dimensions: (LxWxH) 21.75x8x2 "</i></p> <p><i>Waranty: 36 months</i></p>	20		
2.	<p>Memorija 1</p> <p><i>Kapacitet: 2 GB, Tip: DDR 3, Frekvencija: 1600 MHz</i></p> <p><i>Jamstvo 60 mjeseci</i></p> <p><i>latencija, 9-9-9-24</i></p> <p><i>with Classic Heat Spreader</i></p>	15		
3.	<p>Miš</p> <p><i>Interfaces: 1 x USB - 4 pin USB Type A   1 x mouse - generic - 6 pin mini-DIN (PS/2 style)</i></p> <p><i>Color: Black</i></p> <p><i>Orientation: Right and left-handed</i></p> <p><i>Buttons Qty: 3</i></p> <p><i>Connectivity Technology: Wired</i></p> <p><i>Features: Tilt Wheel Plus Zoom, scrolling wheel (4-way)</i></p> <p><i>Interface: USB</i></p> <p><i>Movement Detection Technology: Optical</i></p> <p><i>Movement Resolution: 1000 dpi</i></p> <p><i>Service &amp; Support: 3 years warranty</i></p> <p><i>Cables Included: 1 x USB cable   1 x mouse adapter</i></p>	20		
4.	<p>Ladica 1</p> <p><i>Ladica 3,5" SATA HDD, USB2.0 External, 3,5</i></p> <p><i>Sučelje diska SATA,SATA II</i></p> <p><i>Sučelje ladice USB</i></p> <p><i>Napajanje vanjsko</i></p> <p><i>Hlađenje pasivno</i></p>	5		

5.	Napajanje ATX	20		
	<p>550 W, ATX 2, 120mm ventilator, super silent</p> <p>Connectors: 1x 20/24 pin mainboard, 1x 4/8 pin mainboard, 1x 6 pin PCI-Express, 2x SATA, 4x 4 pin, 1x FDD</p> <p>Jamstvo 24 mjeseca</p>			

6.	Matična ploča	2		
	<p>Chipset Intel® P67(B3) Express Chipset</p> <p>Socket 1155</p> <p>Memory 4 x DIMM, Max. 32 GB, DDR 2200</p> <p>Expansion Slots 4 x PCIe 2.0 x16 (single @x16, dual @x8, triple @x8, x16, x16)</p> <p>1 x PCIe 2.0 x4</p> <p>1 x PCIe 2.0 x1</p> <p>Multi-GPU Support Support NVIDIA® 3-Way SLI™ / ATI CrossFireX™ Technology</p> <p>Bluetooth Bluetooth Module Accessory Card</p> <ul style="list-style-type: none"> <li>- Bluetooth V2.0/V2.1+EDR</li> <li>- RC Bluetooth On/Off Switch</li> </ul> <p>Storage Intel® P67(B3) Express Chipset</p> <p>2 xSATA 6.0 Gb/s ports (Red)</p> <p>4 xSATA 3Gb/s ports (Gray)</p> <p>Intel® Rapid Storage Technology Support RAID 0,1,5,10</p> <p>Marvell® 9182 PCIe SATA6Gb/s controller</p> <p>2 xSATA 6Gb/s ports (Red)</p> <p>JMicron® 362 controller</p> <p>2 xExternal SATA 3Gb/s ports at rear (SATA On-the-Go)</p> <p>LAN 2 x Intel® Gigabit LAN</p> <p>Audio Realtek ALC889 8-Channel High Definition Audio CODEC</p> <ul style="list-style-type: none"> <li>- Blu-ray audio layer Content Protection</li> <li>- Supports Jack-Detection, Multi-streaming, Front Panel Jack-Retasking</li> <li>- Supports 1 x Optical S/PDIF out port at back I/O</li> </ul> <p>USB Intel® P67(B3) Express Chipset</p> <ul style="list-style-type: none"> <li>- 9 x USB 2.0/1.1 ports (8 ports at mid-board, 1 port at rear is also for ROG connect)</li> <li>1 x NEC USB3.0 Controller</li> <li>- 2 x USB 3.0/2.0 ports at rear</li> <li>1 x NEC USB3.0 Controller with 2 x VIA SuperSpeed USB hub controllers:</li> <li>- 6 x USB 3.0/2.0 ports at rear</li> <li>- 2 x USB 3.0/2.0 ports at mid-board for front panel support</li> </ul> <p>Back Panel I/O Ports 1 x PS/2 Keyboard/Mouse Combo port</p> <p>2 x External SATA</p> <p>2 x LAN(RJ45) port(s)</p> <p>8 x USB 3.0/2.0</p> <p>1 x USB 2.0/1.1 (also for ROG Connect)</p>			

1 x S/PDIF Out (Optical)  
8 -Channel Audio I/O  
1 x Clr CMOS switch  
1 x ROG Connect On/Off switch  
1 x RC Bluetooth switch  
Internal I/O Connectors 1 x USB 3.0/2.0 connector(s) (Red) supports additional 2 USB 3.0 ports  
4 x USB 2.0/1.1 connector(s) support additional 8 USB 2.0 ports  
4 x SATA 6.0Gb/s connectors (Red)  
4 x SATA 3.0Gb/s connectors (Gray)  
1 x CPU Fan connector(s)  
3 x Chassis Fan connector(s)  
1 x Power Fan connector(s)  
3 x Optional Fan connector  
1 x Power-on switch  
1 x Reset switch  
1 x S/PDIF Out connector  
1 x 24-pin ATX Power connector  
1 x 8-pin ATX 12V Power connector  
1 x Front panel audio connector  
1 x System Panel connector  
7 x Probelts measurement points  
3 x Thermal sensor connectors  
1 x En/Dis-able Clr CMOS header  
2 x EZ Plug connectors (4-pin Molex Power connectors)  
1 x RC Bluetooth header  
1 x LN2 Mode switch  
1 x Q\_Reset switch  
1 x Go Button  
1 x BIOS switch button  
1 x ROG light connector  
BIOS 32 Mb Flash ROM , EFI AMI BIOS, PnP, DMI2.0, WfM2.0, SM BIOS 2.5, ACPI2.0a Multi-Language BIOS  
Manageability WfM 2.0, DMI 2.0, WOL by PME, WOR by PME, PXE  
Accessories User's manual  
1 2-port USB2.0 module  
1 x I/O Shield  
2 x SATA 3.0Gb/s signal cables (2-in-1)  
2 x SATA 6.0Gb/s signal cables (2-in-1)  
1 x Q-Connecor Kit (2-in-1)  
1 x ROG Connect Cable  
1 x Probelts cable set  
1 x Thermal Sensor Cable Pack  
1 x 3-Way SLI bridge  
1 x SLI Cable

<ul style="list-style-type: none"> <li>1 x Crossfire cable</li> <li>1 x Cable Ties Pack</li> <li>1 x ROG Theme Label</li> <li>1 x 12-in-1 ROG Cable Label</li> <li>1 x RC Bluetooth card</li> <li>1 x ROG exclusive feature guide</li> </ul>	
--	--

7.	CPU	2		
	<ul style="list-style-type: none"> <li>Family Intel Core i7</li> <li>Model number I7-2600K</li> <li>Frequency (MHz) 3400</li> <li>Turbo frequency (MHz) 3800</li> <li>Package 1155-land Flip-Chip Land Grid Array</li> <li>Socket Socket H2 (LGA1155)</li> <li>Microarchitecture Sandy Bridge</li> <li>Manufacturing process 0.032 micron High-K metal gate process</li> <li>Data width 64 bit</li> <li>Number of cores 4</li> <li>Floating Point Unit Integrated</li> <li>Level 1 cache size 4 x 32 KB instruction caches</li> <li>2 x 32 KB data caches</li> <li>Level 2 cache size 4 x 256 KB</li> <li>Level 3 cache size 8 MB shared cache</li> <li>hladjak za procesor: da (box)</li> </ul>			

8.	Grafička kartica 1	2		
	<ul style="list-style-type: none"> <li>GPU: NVIDIA GeForce, GTX570</li> <li>Utor: PCIe x16</li> <li>Memorija: 1280 MB, DDR5, 320-bit,</li> <li>Radni takt GPU 742 MHz,</li> <li>Takt memorije 3800 MHz</li> <li>2x DVI-I, HDTV da, 1x D-sub, 1x Display port, HDMI, 2560x1600,</li> <li>DVI-D-Sub adapter</li> </ul>			

9.	Ladica 2	10		
	<ul style="list-style-type: none"> <li>Ladica 2,5" SATA HDD, USB3.0 External,</li> <li>Sučelje diska SATA,SATA II</li> <li>Sučelje ladice USB 3.0</li> <li>Napajanje preko USB-a</li> <li>Hlađenje pasivno</li> </ul>			

<b>10.</b>	<b>MicroSD kartica</b>	<b>13</b>		
	<i>kapacitet 32 GB</i> <i>Brzina Brzina čitanja: 10 MB/s</i> <i>Brzina zapisivanja: 10 MB/s</i> <i>Dimenzije 15 x 1 x 11 mm, 1.4 g</i> <i>Class 10</i> <i>Uključen memorijski adapter</i>			
<b>11</b>	<b>HDD 1</b>	<b>10</b>		
	<i>Sučelje: sATA II</i> <i>Veličina: 2,5"</i> <i>Kapacitet: 500 GB</i> <i>Brzina vrtnje: 7,200 RPM (nominal)</i> <i>Cache 16 MB</i> <i>Jamstvo: 60 mjeseci</i>			
<b>12</b>	<b>HDD 2</b>	<b>10</b>		
	<i>Sučelje: sATA II</i> <i>Veličina: 2,5"</i> <i>Kapacitet: 1 TB</i> <i>Brzina vrtnje: 7,200 RPM (nominal)</i> <i>Cache 16 MB</i> <i>Jamstvo: 36 mjeseci</i>			
<b>13</b>	<b>HDD 3</b>	<b>5</b>		
	<i>Sučelje: sATA II</i> <i>Veličina: 3,5"</i> <i>Kapacitet: 1 TB</i> <i>Brzina vrtnje: 7,200 RPM (nominal)</i> <i>Cache 64 MB</i> <i>Jamstvo: 60 mjeseci</i>			
<b>14</b>	<b>CMOS BATERIJA</b>	<b>30</b>		
	<i>CR-2032</i> <i>Napon 3V</i> <i>200 mAh</i>			



15	GPS Receiver bluetooth	10		
	<p>MT 3318f +6601</p> <p>GPS single +Bluetooth Chipset</p> <p>Frequency : L1,1575.42MHz</p> <p>C/A code : 1.023MHz Chip rate</p> <p>Channels : 14/32</p> <p>Accuracy</p> <p>3meters,2D RMS</p> <p>2.5meters,2D,RMS WAAS corrected &lt;</p> <p>2.5meters (50%)</p> <p>Velocity : 0.1meters/second</p> <p>Time : 1microsecond synchronized to GPS time</p> <p>Default : WGS-84</p> <p>Other : selectable for other Datum</p> <p>Reacquisition : 0.1sec.,average</p> <p>Hot start : 1sec.,average typical TTFF</p> <p>Warm start : 36sec.,average typical TTFF</p> <p>Coid Start : 38 sec.,average typical TTFF</p> <p>Altitude : 18,000meters(60,000feet) max.</p> <p>Velocity : 515meter/second(1000 knots) max.</p> <p>Acceleration : 4g, max</p> <p>Jerk : 20 meter/second<sup>3</sup>, max.</p>			
16	Kabel 1	10		
	<p>VGA kabel</p> <p>m/m</p> <p>dužina 1.8 m</p> <p>za monitor</p>			
17.	USB memory stick	20		
	<p>Kapacitet: 32 GB</p> <p>sučelje: USB 3.0</p> <p>transfer: for USB 3.0 to 100MB/sec read and 70MB/sec write</p> <p>compatible with USB 2.0</p> <p>Operating Temperature: 32° to 140°F (0°C to 60°C)</p> <p>Jamstvo: 60 mjeseci</p>			

18.	Grafička kartica 2	5		
	<i>Sabirnica: AGP 4x/8x</i> <i>Količina memorije [MB]: 512</i> <i>Memorija: DDR2</i> <i>Memorijsko sučelje: 64-bit</i> <i>Radni takt GPU [MHz]: 600</i> <i>Takt memorije [MHz]: 800</i> <i>Stream procesori: 40</i> <i>Radni takt stream procesora [MHz]: 0</i> <i>RAMDAC [MHz]: 400</i> <i>Max. rezolucija: 2048x1536</i> <i>D-sub (VGA): 1</i> <i>DVI: 1</i> <i>Jamstvo: 24 mjeseca</i>			
19.	Telefonski kabel	1		
	<i>4 x 7 x 0,12 mm 4-žice:</i> <i>bijela, smeđa, zelena, žuta 5,0 mm x 2,0 mm</i> <i>boja. Crna</i> <i>Kolut 100 m</i>			
20.	Produžni usb kabel	20		
	<i>konektori: A-A M/F</i> <i>dužina 1.8 m</i>			
21.	USB KABEL	20		
	<i>konektori: A-A M/M</i> <i>dužina 1.8 m</i>			
22.	TESTER NAPAJANJA	3		
	<ul style="list-style-type: none"> <li>• <i>Voltage source: 20/24 pol. (ATX-connector)</i></li> <li>• <i>Voltage test: +12V, -12V, +5V, +3,3V 5V Stand By (SB), 12V Power Good (PG)</i></li> <li>• <i>Connectors: Floppy, HDD, CDROM, SATA, 4 pin (P4), 8 pin (Dual-CPU), 6 pin (PCI-Express)</i></li> <li>• <i>All supply voltage shows on display with one decimal place</i></li> </ul>			

23.	DVD PISAČ	2		
<p><i>Podržani mediji: CD R, CD RW, DVD+R, DVD+RW, DVD-R, DVD-RW, DVD+R DL, DVD+RW DL, DVD-R DL, DVD-RW DL, DVD-RAM</i></p> <p><i>Sučelje: USB</i></p> <p><i>Brzina čitanja: CD: 24 X</i></p> <p><i>DVD: 8 X</i></p> <p><i>Brzina pisanja: CD R: 24 X</i></p> <p><i>CD RW: 24 X</i></p> <p><i>DVD R: 8 X</i></p> <p><i>DVD RW: 6/8 X</i></p> <p><i>DVD R dvoslojni: 6 X</i></p> <p><i>DVD RAM: 5 X</i></p> <p><i>Ostalo: Tip uređaja: eksterni CD/DVD čitač + CD/DVD pisač</i></p> <p><i>Boja: crna</i></p>				

<b>UKUPNO INFORMATIČKE KOMPONENTE (bez PDV-a):</b>	
[slovima: _____ ]	

### 3. Računalni programi

RAČUNALNI PROGRAMI - SOFTWARE				
Br.	Naziv artikla / specifikacija	Količina	Jedinična cijena	Ukupna cijena
1.	Antivirusni program (mrežna administracija) za 350 klijenata	1		
2.	System Center Essentials 2010 (OLP za 18 servera i 100 klijenata sa uključenim Software Assuranceom)	1		
3.	Office Professional 2010 OLP English	20		
4.	Data Dynamics „Active Reports“ for .net Standard Edition Version 2 upgrade	1		
5.	Verisign SSL Renew	5		
6.	SQL Server 2008 R2 standard za 1 CPU	1		
7.	Microsoft Visual Studio 2010 Professional With MSDN RENEWAL	1		
8.	Microsoft TechNet subscription Professional with media upgrade	3		
9.	Aspose.Words for .NET: Developer Small Business	1		
10.	Cisco CON-SNT-3750G24TS-1	1		
11.	Cisco CON-SU1-AS1A1PK9-1	1		
12.	Cisco CON-SNT-CISC876K-1	1		
13.	Boztek VENM Console 2012 Per-Admin License	2		

**UKUPNO RAČUNALNI PROGRAMI (bez PDV-a):**

[slovima: \_\_\_\_\_]

# REKAPITULACIJA

## Troškovnik

R/Br	Naziv artikla	Količina	Jedinična cijena	Ukupna cijena
<b>1. TEHNIČKA SREDSTVA</b>				
1.	Kopirni uređaj	1		
2.	Monitor	25		
3.	Radna stanica bez monitora	10		
4.	Prijenosno računalo 1	30		
5.	Prijenosno računalo 2	5		
6.	Prijenosno računalo 3	3		
7.	Prijenosno računalo 4	3		
8.	Projektor	1		
9.	Security Applinace	1		
10.	L3 switch	2		
11.	Fotoaparar	1		
12.	Bljeskalica	1		
<b><i>Ukupno tehnička sredstva (bez PDV-a):</i></b>				
<b>2. INFORMATIČKE KOMPONENTE</b>				
1.	Tipkovnica	20		
2.	Memorija 1	15		
3.	Miš	20		
4.	Ladica 1	5		
5.	Napajanje ATX	20		
6.	Matična ploča	2		
7.	CPU	2		
8.	Grafička kartica 1	2		
9.	Ladica 2	10		
10.	MicroSD kartica	13		
11.	HDD 1	10		
12.	HDD 2	10		
13.	HDD 3	5		
14.	CMOS BATERIJA	30		
15.	GPS Receiver bluetooth	10		
16.	Kabel 1	10		
17.	USB memory stick	20		
18.	Grafička kartica 2	5		
19.	Telefonski kabel 100 m	1		
20.	Produžni usb kabel A-A M/F	20		
21.	USB kabel	20		
22.	Tester napajanja	3		
23.	Dvd pisač	2		
<b><i>Ukupno informatičke komponente (bez PDV-a):</i></b>				

2. RAČUNALNI PROGRAMI				
1.	Antivirusni program (mrežna administracija) za 350 klijenata	1		
2.	System Center Essentials 2010 (OLP za 18 servera i 100 klijenata sa uključenim Software Assuranceom)	1		
3.	Office Professional 2010 OLP English	20		
4.	Data Dynamics „Active Reports“ for .net Standard Edition Version 2 upgrade	1		
5.	Verisign SSL Renew	5		
6.	SQL Server 2008 R2 standard	1		
7.	Microsoft Visual Studio 2010 Professional With MSDN RENEWAL	1		
8.	Microsoft TechNet subscription Professional with media upgrade	3		
9.	Aspose.Words for .NET: Developer Small Business	1		
10.	Cisco CON-SNT-3750G24TS-1	1		
11.	Cisco CON-SU1-AS1A1PK9-1	1		
12.	Cisco CON-SNT-CISC876K-1	1		
13.	Bozteck VENM Console 2012 Per-Admin License	2		
<b>Ukupno računalni programi (bez PDV-a):</b>				
<b>CIJENA PONUDE (ukupno tehnička sredstva, informatičke komponente i računalni programi) bez PDV-a:</b>				
Slovima:				
<b>Popust _____ %</b>				
<b>CIJENA PONUDE (ukupno tehnička sredstva, informatičke komponente i računalni programi) bez PDV-a s popustom:</b>				
Slovima:				
<b>Iznos PDV-a:</b>				
<b>UKUPNA CIJENA PONUDE s popustom i PDV-om:</b>				
Slovima:				

**OPĆI PODACI O PONUDITELJU / IMA:**

Naziv: \_\_\_\_\_

Sjedište: \_\_\_\_\_

MB: \_\_\_\_\_ OIB: \_\_\_\_\_

Tel: \_\_\_\_\_ Fax: \_\_\_\_\_ Mob: \_\_\_\_\_

Odgovorna / e osoba: \_\_\_\_\_

Osoba / e za kontakte i tel: \_\_\_\_\_

Mjesto i datum: \_\_\_\_\_

Potpis / i štambilj / i ponuditelja:

\_\_\_\_\_

## Pregled uređaja prema proizvođaču, distributeru i ovlaštenom servisu

R/Br	Naziv artikla	Proizvođač	Distributer	Naziv servisa i adresa
1.	Kopirni uređaj			
2.	Monitor			
3.	Radna stanica bez monitora			
4.	Prijenosno računalo 1			
5.	Prijenosno računalo 2			
6.	Prijenosno računalo 3a 15,6"			
7.	Prijenosno računalo 3b 17,3"			
8.	Projektor			
9.	Security Appliance			
10.	L3 switch			
11.	Fotoaparat			
12.	Bljeskalica			
13.	Tipkovnica			
14.	Memorija 1			
15.	Miš			
16.	Ladica 1			
17.	Napajanje ATX			
18.	Matična ploča			
19.	CPU			
20.	Grafička kartica 1			
21.	Ladica 2			
22.	MicroSD kartica			
23.	HDD 1			
24.	HDD 2			
25.	HDD 3			
26.	CMOS BATERIJA			
27.	GPS Receiver bluetooth			
28.	Kabel 1			
29.	USB memory stick			

30.	Grafička kartica 2			
31.	Telefonski kabel 100 m			
32.	Produžni usb kabel A-A M/F			
33.	USB kabel			
34.	Tester napajanja			
35.	Dvd pisac			

**OPĆI PODACI O PONUDITELJU / IMA:**

Naziv i sjedište (MB, OIB): \_\_\_\_\_

Odgovorna / e osoba: \_\_\_\_\_

Mjesto i datum: \_\_\_\_\_

Potpis / i štambilj / i ponuditelja:

\_\_\_\_\_