

PRIVITAK 2 - TROŠKOVNIK (TEHNIČKA SPECIFIKACIJA)

OSTALA OPREMA

Red. Br.	Naziv artikla / specifikacija	Jedinica mjere	Kol.	Jedinična cijena	Cijena bez PDV-a
	Projektor				
	Display Technology	Single 0.67" DarkChip 3 WUXGA DLP® Technology by Texas Instruments			
	Native Resolution	WUXGA 1920 x 1200			
	Brightness1 (Bright Mode)	4200 ANSI Lumens			
	Contrast	20,000:1			
	Lamp Life2 Eco+/Dynamic/Eco/Brig ht	7000/6000/5000/3000 (hrs)			
	Throw Ratio 3	1.4 - 2.24:1			
	Zoom Type	1.6x Manual			
	Lens Shift	+13% Vertical			
	I/O Connectors	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service			
	Speaker	10			
	Keystone Correction	± 40° Vertical			
	Weight (kg)	2,99			
	Dimensions (W x D x H) (mm)	314 x 2246 x 114			
	Aspect Ratio	16:10 Native, 16:9/4:3 Compatible			
	Offset	94% ~ 107%			
	Projection Screen Size	0.68 – 7.75m (26.94" - 305.1") Diagonal 16:10			
	Projection Distance	1.3 - 9.2m			
	Projection Lens	F/2.5~3.26; f=20.91~32.62mm			
	Uniformity	70%			

1.	Computer Compatibility	WUXGA, FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac	kom	2	
	Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p			
	3D Support	Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.			
	3D Compatibility	Side-by-Side:1080i50 / 60, 720p50 / 60			
		Frame-pack: 1080p24, 720p50 / 60			
		Over-Under: 1080p24, 720p50 / 60			
	Horizontal Scan Rate	15 - 91kHz			
	Vertical Scan Rate	24 - 120Hz			
	Displayable Colours	1.07 Billion			
	Noise Level (Eco mode)	32dB			
	Power Supply	100-240V, 50-60Hz			
	Power Consumption	309W Bright mode / 249W Eco mode (<0.5W Standby)			
	Lamp Type	260W			
	Security	Kensington lock, password protection			
	On Screen Display	19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Arabic, Turkish, Farsi, Romanian			
	Standard Accessories	AC power cord, remote control, 2x AAA batteries, quick start card, CD user manual			
	Optional Accessories	DLP® Link™ 3D glasses, wireless, ceiling mount			
	Optional Wireless	Yes			
	RoHS	Compliant			
	Jamstvo	3 godine (lampa12 mjeseci)			

2.	Dock univerzalni				
	Specifikacija	Extends 1x USB 3.0 to 11 further interfaces	kom	5	
		Input: (to Notebook / PC):			
		USB 3.0 type B female			
		Output:			
		2x USB 3.0 type A female			
		Including 1x USB 3.0 5 V charger for Smartphone / Tablet			
		1x Microphone 3.5 mm jack			
		1x Earphone 3.5 mm jack			
		1x HDMI Connector			
		1x DVI-I (Dual-Link) 24+5 female			
		1x Gigabit LAN RJ45 female			
		4x USB 2.0 type A female			
		Inklusiv einen DVI zu VGA Adapter			
		HDMI and DVI ports support:			
		mirroring and extending of the display, Resolution up to 2048x1152 Pi			
		USB 3.0 backwards compatible with USB 2.0			
Vertical (with stand foot) und horizontal settable					
Plug & Play and Hot Swap					
Power adapter (100 240V), 5 V/4 A, 20 W					
	NAS s diskovima				
	Technical specifications				
	Hardware				
	CPU	Marvell ARMADA 385 88F6820 dual-core 1.8GHz			
	Hardware encryption engine	Yes			
	Floating point unit	Yes			
	RAM size	DDR3 1GB			
	Compatible drive type	3.5"/2.5" SATA III/II x 4 (hard drives not included)			

Maximum internal raw capacity	32TB (8TB HDD x 4) (actual capacity depending on volume types)
External ports	USB 3.0 port x 2, eSATA port x 1
Size (HxWxD)	44 mm x 430.5 mm x 290 mm
Weight	4.34 kg
LAN	Gigabit (RJ-45) x 2
Wake on LAN/WAN	Yes
Scheduled power on/off	Yes
AC input power voltage	100V to 240V
Power frequency	50Hz to 60Hz, single phase
Operating temperature	5°C to 35°C (40°F to 95°F)
Storage temperature	-20°C to 60°C (-5°F to 140°F)
Relative humidity	5% to 95% RH
General	
Networking protocols	CIFS, AFP, NFS, FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN™, L2TP)
File system	Internal: ext4 External: ext4, ext3, FAT, NTFS, HFS+ (read only)
Storage management	Maximum single volume size: 16TB, Maximum internal volume: 256, Maximum iSCSI Target: 10, Maximum iSCSI LUN: 256
Supported RAID type	Hybrid RAID (SHR), Basic, JBOD, RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
File sharing capability	Maximum user account: 2048, Maximum group: 256, Maximum shared folder: 256, Maximum concurrent CIFS/AFP/FTP/File Station connection: 256
Privilege	Windows Access Control List (ACL)
Directory service	Windows AD Integration: Domain Users login via Samba (CIFS)/AFP/FTP/File Station, LDAP integration
Security	FTP over SSL/TLS, IP auto-block, firewall, encrypted network backup over Rsync, HTTPS connection

3.

Utilities	Synology Web Assistant, Cloud Station Drive, Cloud Station Backup, Cloud Sync Decryption Tool, Evidence Integrity Authenticator, Photo Station Uploader
Supported clients	Windows 7 onwards and Mac OS X® 10.10 onwards
Supported browsers	Chrome™, Firefox®, Internet Explorer® 9 onwards, Safari® 8 onwards, Safari (iOS® 7 onwards on iPad®), Chrome (Android 4.0 onwards on tablets)
Language	English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, , Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Český,
Applications	
File Station	Virtual drive, remote folder, Windows ACL editor, compress/extract archived files, bandwidth control for specific users or groups, create sharing links, transfer logs
Backup solutions	Network backup; local backup; desktop backup; configuration backup; OS X Time Machine; backup data to public cloud; shared folder sync - maximum task number: 4
FTP Server	Bandwidth control for TCP connections, custom FTP passive port range, anonymous FTP, FTP SSL/TLS and SFTP protocols, boot over the network with TFTP and PXE support, transfer logs
Printer Server	Maximum printer: 2, printing protocols: LPR, CIFS, IPP, iOS printing, Google Cloud Print™, multi functional print server (MFP functions are for Windows PC only)
Security Advisor	Malware detection/removal, user account/password, network, system-related security scan
iOS/Android™ applications	DS cloud, DS file, DS finder, DS cam, DS note, DS audio, DS download, DS photo, DS video
Windows Phone® applications	DS file, DS finder, DS audio, DS download, DS photo, DS video
Warranty	3 Years
DISKOVI:	

kom

1

Komada	4
Specifikacija:	
Interface	SATA 6 Gb/s
Formatted capacity	8 TB
Form factor	3.5-inch
Advanced Format (AF)	Yes
Native command queuing	Yes
RoHS compliant	Yes
Data transfer rate (max)	
Interface speed	6 Gb/s
Internal transfer rate	178 MB/s
Cache (MB)	128
Performance Class	5400 RPM Class
Load/unload cycles	600,000
Non-recoverable read errors p	<1 in 10 ¹⁴
MTBF (hours)	1,000,000
Limited warranty (years)	3
Power Management	
12VDC ±10% (A, peak)	1,79
Average power requirements (W)	
Read/Write	6,4
Idle	5,2
Standby/Sleep	0,7
Shock (Gs)	
Operating (2 ms, read/write)	30
Operating (2 ms, read)	65
Non-operating (2 ms)	250
Acoustics (dBA)9	
Idle	20
Seek (average)	29
Warranty (years)	3

4.	LTO 7 tape		kom	10		
	Specifikacija	Media type: Linear serpentine recording half-inch cartridge				
		Data capacity: 6 TB native				
		Up to 15 TB with 2.5:1 data compression				
	Cartridge models: LTO Ultrium 7 6 TB rewritable data cartridge					
5.	Tablet		kom	1		
	Technical specifications					
	Technology	GSM / HSPA / LTE				
	2G bands	GSM 850 / 900 / 1800 / 1900				
	3G bands	HSDPA 850 / 900 / 1900 / 2100				
	4G bands	LTE band 1(2100), 2(1900), 3(1800), 4(1700/2100), 5(850), 7(2600), 8(900), 17(700), 20(800), 28(700), 40(2300)				
	Speed	HSPA 42.2/5.76 Mbps, LTE-A (2CA) Cat6 300/50 Mbps				
	GPRS	Yes				
	EDGE	Yes				
	Dimensions	237.3 x 169 x 6 mm (9.34 x 6.65 x 0.24 in)				
	Weight	429 g (Wi-Fi)/ 434 g (LTE) (15.13 oz)				
	SIM	Nano-SIM				
		- Stylus				
	Type	Super AMOLED capacitive touchscreen, 16M colors				
	Size	9.7 inches (~72.7% screen-to-body ratio)				
	Resolution	1536 x 2048 pixels (~264 ppi pixel density)				
	Multitouch	Yes, up to 5 fingers				
	OS	Android 7.0 (Nougat)				
	Chipset	Qualcomm MSM8996 Snapdragon 820				
	CPU	Quad-core (2x2.15 GHz Kryo & 2x1.6 GHz Kryo)				
	GPU	Adreno 530				
	Card slot	microSD, up to 256 GB (dedicated slot)				
	Internal	32 GB, 4 GB RAM				
Primary	13 MP, f/1.9, 27mm, autofocus, LED flash					
Features	Geo-tagging, touch focus, face detection, HDR, panorama					
Video	2160p@30fps					
Secondary	5 MP, f/2.2, 23mm, 1080p					
Alert types	Vibration; MP3, WAV ringtones					
Loudspeaker	Yes, with stereo speakers (4 speakers)					
3.5mm jack	Yes					

	- Speakers tuned by AKG/HARMAN			
	WLAN	Wi-Fi 802.11 a/b/g/n/ac, dual-band, Wi-Fi Direct, hotspot		
	Bluetooth	4.2, A2DP, LE		
	GPS	Yes, with A-GPS, GLONASS, BDS, GALILEO		
	Radio	No		
	USB	3.1, Type-C 1.0 reversible connector; magnetic connector		
	Dodatno:			
	Book Cover	Dark Gray		
		EJ-FT820BSEGGB		
6.	Punjač za prijenosno računalo		kom	5
		Input 220 V		
		Output 19.5 V DC, 2.32 A		
		Power 45 W		
		P/N 04H6NV		
CIJENA PONUDE BEZ PDV-a:				
Iznos PDV-a:				
UKUPNA CIJENA PONUDE S PDV-om:				

(mjesto i datum)

M.P.

(Potpis ovlaštene osobe)